


FLAT

Insulated Metal Panel

TC Flat is the preferred exterior wall panel for creating a high-profile architectural appearance for commercial and industrial buildings, including manufacturing, dry goods distribution centers, automotive assembly plants, aircraft hangers, offices, and schools.

Expertly crafted by industry veterans, you can rely on TrueCore's Flat for problem-free construction and building operation.

SIDE JOINT



PANEL PROFILE AND CROSS SECTION



EXTERIOR AND INTERIOR PROFILE & TEXTURE

Flat profile with non-directional stucco embossing

EXTERIOR FACINGS

22 Ga. G-90 galvanized steel or AZ50 aluminum coated steel

INTERIOR FACINGS

26, 24, 22 Ga. G-90 galvanized steel or AZ50 aluminum coated steel

26, 24 Ga. 304L and 316L stainless steel with 2B finish

EXTERIOR COATINGS

Siliconized Polyester (SMP)
Fluoropolymer(PVDF)
Flurothane* II, IV, V

INTERIOR COATINGS

Polyester
Siliconized Polyester (SMP)
Fluoropolymer (PVDF)
Flurothane* II, IV, V
PVC Plastisol

WIDTH

40", 36"

LENGTH

8'-0" to 32'-0" standard
Contact TrueCore for information and pricing on longer lengths.

THICKNESS

2", 3", 4"

CORE

Foamed-in-place Class 1 rated polyisocyanurate

JOINT

Double Tongue and Groove for concealed fastening

R-VALUE

R-8 per inch of thickness (nominal)

*Flurothane is a registered trademark of The Sherwin-Williams Company